



Anthony Spot Track 1-10V Version

03.8023.40.1V - White


Accent lighting LED module to be installed in The Tracking Magnet System.

Main specifications

Number of heads	1	Net lumen (lm)	1129
Lamp category	LED	Mountings	Track
Power (W)	16W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



Beam Angle: 22°

h(m)	E(lx)	D(m)
1	5910	0.40
2	1478	0.79
3	657	1.19
4	369	1.58
5	236	1.98

Luminous flux luminaire
1129 lm



Electrical


Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable 1-10V		
Emergency	Without		

Physical

Color	White	Spot diameter (mm)	110
Orientation	Adjustable		
Weight (kg)	0.43		
Tilt (°)	90		
Rotation (°)	360		

Note

Only compatible with DALI, 1-10V, FLOS SMART CONTROL profile version.



Anthony Spot Track 1-10V Version



Elliptical lens
08.8418.68A

Honeycomb
08.8419.14A

Flood lens
08.0050.00