


## Anthony Spot Track Casambi integrated

New

03.6274.40ACB - White

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 1085                |
| Power (W)        | 16W   | Mountings      | Track               |
| System power (W) | 16.5  | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 15        |
| Beam angle C90-270 (°) | 15        |
| UGRL                   | 11        |
| Efficiency (lm/W)      | 65.76     |



Beam Angle: 15°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 11592 | 0.27 |
| 2    | 2898  | 0.54 |
| 3    | 1288  | 0.81 |
| 4    | 724   | 1.09 |
| 5    | 464   | 1.36 |

Luminous flux luminaire  
1085 lm

### Electrical

|             |                 |                  |     |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 24.00           | Insulation class | III |
| Dimmable    | Yes             |                  |     |
| Driver      | Remote excluded |                  |     |
| Driver type | Dimmable        |                  |     |
| Emergency   | Casambi         |                  |     |
|             | Without         |                  |     |

### Physical

|              |            |                    |        |
|--------------|------------|--------------------|--------|
| Color        | White      | Spot diameter (mm) | 110    |
| Orientation  | Adjustable | Length (mm)        | 130    |
| Weight (kg)  | 0.36       | Lifespan (L70 B10) | L80B50 |
| Tilt (°)     | 90         |                    |        |
| Rotation (°) | 360        |                    |        |

### Note

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



## Anthony Spot Track Casambi integrated



---

Flood lens  
08.0050.00



---

Elliptical lens  
08.8418.68A



---

Honeycomb  
08.8419.14A