

Anthony Spot Track Casambi integrated

New

03.6275.14ACB - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	1129
Power (W)	16W	**Mountings**	Track
System power (W)	16.5	**Environment**	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22
UGRL	11
Efficiency (lm/W)	68.42



Luminous flux luminaire
1129 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	5910	0.40
2	1478	0.79
3	657	1.19
4	369	1.58
5	236	1.98

Electrical

Voltage (V)	24.00	**Insulation class**	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		
Emergency	Without		

Physical

Color	Black	**Spot diameter (mm)**	110
Orientation	Adjustable	**Length (mm)**	130
Weight (kg)	0.36	**Lifespan (L70 B10)**	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

IP 20 RETILAP GWT 850°

Anthony Spot Track Casambi integrated

Elliptical lens
08.8418.68A

Honeycomb
08.8419.14A

Flood lens
08.0050.00