


Anthony Spot Track Casambi integrated

New

■ 03.6275.14ACB - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




Main specifications

Number of heads	1	Net lumen (lm)	1129
Lamp category	LED	Mountings	Track
Power (W)	16W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



Beam Angle:	22°		
h(m)	E(lx)	D(m)	
1	5910	0.40	
2	1478	0.79	
3	657	1.19	
4	369	1.58	
5	236	1.98	

Luminous flux luminaire
1129 lm

Electrical


Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
	Casambi		
Emergency	Without		

Physical

Color	Black	Spot diameter (mm)	110
Orientation	Adjustable	Length (mm)	130
Weight (kg)	0.36		
Tilt (°)	90		
Rotation (°)	360		

Note

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



Anthony Spot Track Casambi integrated



Flood lens
08.0050.00



Elliptical lens
08.8418.68A



Honeycomb
08.8419.14A