


Anthony Spot Track Casambi integrated

New

03.6277.40ACB - White

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1010
Power (W)	16W	Mountings	Track
System power (W)	16.5	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15
UGRL	10
Efficiency (lm/W)	61.21



Beam Angle: 15°

h(m) E(lx) D(m)

1 10798 0.27

2 2700 0.54

3 1200 0.81

4 675 1.09

5 432 1.36

Luminous flux luminaire
1010 lm

Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

Physical

Color	White	Spot diameter (mm)	110
Orientation	Adjustable	Length (mm)	130
Weight (kg)	0.36	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



Anthony Spot Track Casambi integrated



Elliptical lens
08.8418.68A

Honeycomb
08.8419.14A

Flood lens
08.0050.00