


## Anthony Spot Track Casambi integrated

New

03.6278.40ACB - White

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




## Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1052
Power (W)	16W	Mountings	Track
System power (W)	16.5	Environment	Indoor dry location
CCT (K)	2700K		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22
UGRL	11
Efficiency (lm/W)	63.76



Beam Angle: 22°

h(m)	E(lx)	D(m)
1	5506	0.40
2	1376	0.79
3	612	1.19
4	344	1.58
5	220	1.98

Luminous flux luminaire  
1052 lm

## Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

## Physical

Color	White	Spot diameter (mm)	110
Orientation	Adjustable	Length (mm)	130
Weight (kg)	0.36	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

## Note

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



## Anthony Spot Track Casambi integrated



---

Elliptical lens  
08.8418.68A

---

Honeycomb  
08.8419.14A

---

Flood lens  
08.0050.00