



Anthony Spot Track Casambi integrated

New

03.8028.14.CB - Black


Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED array	Net lumen (lm)	1426
Power (W)	16.5W	Mountings	Track
System power (W)	17.6	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28
UGRL	12
Efficiency (lm/W)	81.02



Beam Angle: 28°

h(m)	E(lx)	D(m)
1	5907	0.49
2	1477	0.98
3	656	1.47
4	369	1.97
5	236	2.46

Luminous flux luminaire
1426 lm

Electrical


Voltage (V)	48	Emergency	Without
Current (mA)	450	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
	Casambi		

Physical

Color	Black	Spot diameter (mm)	110
Orientation	Adjustable	Length (mm)	178
Weight (kg)	0.43	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



Anthony Spot Track Casambi integrated



Elliptical lens
08.8418.68A

Honeycomb
08.8419.14A

Flood lens
08.0050.00