



## Anthony Spot Track Casambi integrated

New

03.8028.40.CB - White


Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1426
Power (W)	16.5W	Mountings	Track
System power (W)	17.6	Environment	Indoor dry location
CCT (K)	3000K		

### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28
UGRL	12
Efficiency (lm/W)	81.02



Beam Angle: 28°

h(m)	E(lx)	D(m)
1	5907	0.49
2	1477	0.98
3	656	1.47
4	369	1.97
5	236	2.46

Luminous flux luminaire  
1426 lm



### Electrical

Voltage (V)	48	Emergency	Without
Current (mA)	450	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
	Casambi		

### Physical

Color	White	Spot diameter (mm)	110
Orientation	Adjustable	Length (mm)	178
Weight (kg)	0.43	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



## Anthony Spot Track Casambi integrated



---

Elliptical lens  
08.8418.68A

---

Honeycomb  
08.8419.14A

---

Flood lens  
08.0050.00