

## Anthony Spot Track Dali Version

03.6275.40ADA - White

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1129
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	16W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	22
<b>Beam angle C90-270 (°)</b>	22



<b>Beam Angle:</b>	22°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	5910	0.40	
2	1478	0.79	
3	657	1.19	
4	369	1.58	
5	236	1.98	

Luminous flux luminaire  
1129 lm



### Electrical


<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	110
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	130
<b>Weight (kg)</b>	0.36		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

To obtain flood optics (35°) order Anthony Spot Medium + flood lens. For wireless lighting control, choose integrated Casambi versions.



## Anthony Spot Track Dali Version



---

Flood lens  
08.0050.00

Honeycomb  
08.8419.14A

Elliptical lens  
08.8418.68A