



Anthony Spot Track Dimmable 1-10V

■ 03.8025.14.1V - Black


Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.

Main specifications

| | | | |
|------------------------|-------|-----------------------|--------|
| Number of heads | 1 | Net lumen (lm) | 1241 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 16.5W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |


Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 15 |
| Beam angle C90-270 (°) | 15 |



| | | |
|--------------------|--------------|-------------|
| Beam Angle: | 15° | |
| h(m) | E(lx) | D(m) |
| 1 | 12442 | 0.27 |
| 2 | 3110 | 0.54 |
| 3 | 1382 | 0.81 |
| 4 | 778 | 1.07 |
| 5 | 498 | 1.34 |

Luminous flux luminaire
1241 lm



Electrical


| | | | |
|--------------------|------------|-------------------------|-----|
| Voltage (V) | 48.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|---------------------------|-----|
| Color | Black | Spot diameter (mm) | 110 |
| Orientation | Adjustable | | |
| Weight (kg) | 0.43 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Only compatible with 1-10V profile version. For wireless lighting control, choose integrated Casambi versions.



Anthony Spot Track Dimmable 1-10V



Honeycomb
08.8419.14A



Flood lens
08.0050.00



Elliptical lens
08.8418.68A