

## Anthony Spot Track Dimmable 1-10V

03.8026.40.1V - White

Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1242                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Track               |
| <b>Power (W)</b>       | 16.5W | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 2700K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |


### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | LED array |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Medium    |
| <b>Beam angle (°)</b>         | 28        |
| <b>Beam angle C90-270 (°)</b> | 28        |



|                    |              |             |
|--------------------|--------------|-------------|
| <b>Beam Angle:</b> | 28°          |             |
| <b>h(m)</b>        | <b>E(lx)</b> | <b>D(m)</b> |
| 1                  | 5145         | 0.49        |
| 2                  | 1286         | 0.98        |
| 3                  | 572          | 1.47        |
| 4                  | 322          | 1.97        |
| 5                  | 206          | 2.46        |

Luminous flux luminaire  
1242 lm



### Electrical


|                    |                 |                         |     |
|--------------------|-----------------|-------------------------|-----|
| <b>Voltage (V)</b> | 48.00           | <b>Insulation class</b> | III |
| <b>Dimmable</b>    | Yes             |                         |     |
| <b>Driver</b>      | Remote excluded |                         |     |
| <b>Driver type</b> | Dimmable 1-10V  |                         |     |
| <b>Emergency</b>   | Without         |                         |     |

### Physical

|                     |            |                           |     |
|---------------------|------------|---------------------------|-----|
| <b>Color</b>        | White      | <b>Spot diameter (mm)</b> | 110 |
| <b>Orientation</b>  | Adjustable |                           |     |
| <b>Weight (kg)</b>  | 0.43       |                           |     |
| <b>Tilt (°)</b>     | 90         |                           |     |
| <b>Rotation (°)</b> | 360        |                           |     |

### Note

Only compatible with 1-10V profile version. For wireless lighting control, choose integrated Casambi versions.



## Anthony Spot Track Dimmable 1-10V



---

Elliptical lens  
08.8418.68A

---

Honeycomb  
08.8419.14A

---

Flood lens  
08.0050.00