



## Anthony Spot Track Dimmable 1-10V

03.8027.05.1V - Chrome


Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 1425                |
| Power (W)        | 16.5W | Mountings      | Track               |
| System power (W) | 17.6  | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 15        |
| Beam angle C90-270 (°) | 15        |
| UGRL                   | 11        |
| Efficiency (lm/W)      | 80.97     |



Beam Angle: 15°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 14285 | 0.27 |
| 2    | 3571  | 0.54 |
| 3    | 1587  | 0.81 |
| 4    | 893   | 1.07 |
| 5    | 571   | 1.34 |

Luminous flux luminaire  
1425 lm



### Electrical


|              |                 |                  |         |
|--------------|-----------------|------------------|---------|
| Voltage (V)  | 48              | Emergency        | Without |
| Current (mA) | 450             | Insulation class | III     |
| Dimmable     | Yes             |                  |         |
| Driver       | Remote excluded |                  |         |
| Driver type  | Dimmable 1-10V  |                  |         |

### Physical

|              |            |                    |        |
|--------------|------------|--------------------|--------|
| Color        | Chrome     | Spot diameter (mm) | 110    |
| Orientation  | Adjustable | Length (mm)        | 178    |
| Weight (kg)  | 0.43       | Lifespan (L70 B10) | L80B50 |
| Tilt (°)     | 90         |                    |        |
| Rotation (°) | 360        |                    |        |

### Note

Only compatible with 1-10V profile version. For wireless lighting control, choose integrated Casambi versions.



Anthony Spot Track Dimmable 1-10V



---

Elliptical lens  
08.8418.68A

---

Honeycomb  
08.8419.14A

---

Flood lens  
08.0050.00