



Anthony Spot Track Dimmable 1-10V

■ 03.8028.05.1V - Chrome


Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1426
Power (W)	16.5W	Mountings	Track
System power (W)	17.6	Environment	Indoor dry location
CCT (K)	3000K		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28
UGRL	12
Efficiency (lm/W)	81.02



Beam Angle: 28°

h(m)	E(lx)	D(m)
1	5907	0.49
2	1477	0.98
3	656	1.47
4	369	1.97
5	236	2.46

Luminous flux luminaire
1426 lm



Electrical


Voltage (V)	48	Emergency	Without
Current (mA)	450	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable 1-10V		

Physical

Color	Chrome	Spot diameter (mm)	110
Orientation	Adjustable	Length (mm)	178
Weight (kg)	0.43	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Only compatible with 1-10V profile version. For wireless lighting control, choose integrated Casambi versions.



Anthony Spot Track Dimmable 1-10V



Flood lens
08.0050.00

Elliptical lens
08.8418.68A

Honeycomb
08.8419.14A