

Anthony Spot Track On Board Dimmer

■ 03.6275.14A - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1129 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 16W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 22 |
| Beam angle C90-270 (°) | 22 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 22° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 5910 | 0.40 | |
| 2 | 1478 | 0.79 | |
| 3 | 657 | 1.19 | |
| 4 | 369 | 1.58 | |
| 5 | 236 | 1.98 | |

Luminous flux luminaire
1129 lm



Electrical


| | | | |
|--------------------|-----------------|-------------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|---------------------------|-----|
| Color | Black | Spot diameter (mm) | 110 |
| Orientation | Adjustable | Length (mm) | 130 |
| Weight (kg) | 0.36 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. For wireless lighting control, choose integrated Casambi versions.



Anthony Spot Track On Board Dimmer



Elliptical lens
08.8418.68A

Honeycomb
08.8419.14A

Flood lens
08.0050.00