



Anthony Spot Track On Board Dimmer

■ 03.6277.14A - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

| | | | |
|------------------|-------|----------------|---------------------|
| Number of heads | 1 | CRI | 90 |
| Lamp category | LED | Net lumen (lm) | 1010 |
| Power (W) | 16W | Mountings | Track |
| System power (W) | 16.5 | Environment | Indoor dry location |
| CCT (K) | 2700K | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 15 |
| Beam angle C90-270 (°) | 15 |
| UGRL | 10 |
| Efficiency (lm/W) | 61.21 |



Beam Angle: 15°

h(m) E(lx) D(m)

| | | |
|---|-------|------|
| 1 | 10798 | 0.27 |
| 2 | 2700 | 0.54 |
| 3 | 1200 | 0.81 |
| 4 | 675 | 1.09 |
| 5 | 432 | 1.36 |

Luminous flux luminaire
1010 lm

Electrical


| | | | |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmer on board | | |
| Emergency | Without | | |

Physical

| | | | |
|--------------|------------|--------------------|--------|
| Color | Black | Spot diameter (mm) | 110 |
| Orientation | Adjustable | Length (mm) | 130 |
| Weight (kg) | 0.36 | Lifespan (L70 B10) | L80B50 |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. For wireless lighting control, choose integrated Casambi versions.



Anthony Spot Track On Board Dimmer



Elliptical lens
08.8418.68A

Honeycomb
08.8419.14A

Flood lens
08.0050.00