



Atom 120

09.3840.06A - Chrome


Accent lighting LED module. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	355
Power (W)	6W	Mountings	Track
System power (W)	6	Environment	Indoor dry location
CCT (K)	3000K		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14
UGRL	5
Efficiency (lm/W)	59.17



Beam Angle: 14°

	h(m)	E(lx)	D(m)
1	4677	0.25	
2	1169	0.49	
3	520	0.74	
4	292	0.98	
5	187	1.23	

Luminous flux luminaire
355 lm



Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	450	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		

Physical

Color	Chrome	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	33
Weight (kg)	0.22	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories included (honeycomb and screening crosspiece).

