



## Atom 120

### 09.3841.1A - Anodic Ice


LED accent lighting module to be installed in the Diversion system. Electronic DC/DC converter incorporated. System controlled by 1-10V, DALI or Casambi. Broadcast control system. Dimmer not included. To individually control the spots via Casambi, choose the Casambi version of spots. Accessories included (honeycomb and screening crosspiece).

### Main specifications

Number of heads	1	Net lumen (lm)	433
Lamp category	LED	Mountings	Track
Power (W)	8W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

### Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle: 13°

	h(m)	E(lx)	D(m)
1	5843	0.24	
2	1461	0.48	
3	649	0.72	
4	365	0.95	
5	234	1.19	

Luminous flux luminaire  
433 lm



### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable CASAMBI, Electronic dimmable 1-10V, Electronic dimmable DALI		

### Emergency

Without

### Physical

Color	Anodic Ice	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	123
Weight (kg)	0.16		
Tilt (°)	90		
Rotation (°)	360		

