



Atom 120

09.3842.1A - Anodic Ice

LED accent lighting module to be installed in the Diversion system. Electronic DC/DC converter incorporated. System controlled by 1-10V, DALI or Casambi. Broadcast control system. Dimmer not included. To individually control the spots via Casambi, choose the Casambi version of spots. Accessories included (honeycomb and screening crosspiece).


Main specifications

Number of heads	1	Net lumen (lm)	373
Lamp category	LED	Mountings	Track
Power (W)	8W	Environment	Indoor
CCT (K)	3000K		
CRI	90		




Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20



Beam Angle:	20°		
h(m)	E(lx)	D(m)	
1	2624	0.35	
2	656	0.70	
3	292	1.06	
4	164	1.41	
5	105	1.76	


Luminous flux luminaire
373 lm



Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable CASAMBI, Electronic dimmable 1-10V, Electronic dimmable DALI		
Emergency	Without		

Certification / Marking



Physical

Color	Anodic Ice	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	123
Weight (kg)	0.16		
Tilt (°)	90		
Rotation (°)	360		