



Atom 120

09.3842.CZ - Bronze


 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

Main specifications

Number of heads	1	Net lumen (lm)	373
Lamp category	LED	Mountings	Track
Power (W)	8W	Environment	Indoo
CCT (K)	3000K		
CRI	90		

Optical

Lighting type LED type Light distribution Direct Power LED Symmetric Optical type
Beam angle (°)
Beam angle C90-270 (°) Medium 20 20



Luminous flux luminaire 373 lm

Insulation class

Bear	Beam Angle:	
h(m)	E(l ×)	D(m)
1	2624	0.35
2	656	0.70
3	292	1.06
4	164	1.41
5	105	1.76

Electrical

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
Driver type	Electronic,
	Electronic
	dimmable
	CASAMBI,
	Electronic
	dimmable 1-
	10V, Electronic
	dimmable DALI

Without

Emergency

Physical

Color	Bronze	Spot diameter (mm) 33
Orientation	Adjustable	Length (mm) 33
Weight (kg)	0.22	-
Tilt (°)	90	
Rotation (°)	360	

Note

Accessories included (honeycomb and screening crosspiece).