



## Atom 120

09.3843.06 - Chrome


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 298    |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 6W    | Environment    | Indoor |
| CCT (K)         | 2700K |                |        |
| CRI             | 90    |                |        |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 20        |
| Beam angle C90-270 (°) | 20        |



Beam Angle: 20°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2557  | 0.35 |
| 2    | 639   | 0.70 |
| 3    | 284   | 1.06 |
| 4    | 160   | 1.41 |
| 5    | 102   | 1.76 |

Luminous flux luminaire  
364 lm



### Electrical

|             |                                                                                                       |                  |     |
|-------------|-------------------------------------------------------------------------------------------------------|------------------|-----|
| Voltage (V) | 24.00                                                                                                 | Insulation class | III |
| Dimmable    | Yes                                                                                                   |                  |     |
| Driver      | Remote                                                                                                |                  |     |
| Driver type | Electronic,<br>Electronic dimmable<br>CASAMBI,<br>Electronic dimmable 1-10V, Electronic dimmable DALI |                  |     |
|             | Without                                                                                               |                  |     |

### Emergency

### Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | Chrome     | Spot diameter (mm) | 33 |
| Orientation  | Adjustable | Length (mm)        | 33 |
| Weight (kg)  | 0.22       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

### Note

Accessories included (honeycomb and screening crosspiece).