Atom 120

09.3843.06A - Chrome

Accent lighting LED module. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.



Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	298
Power (W)	6W	**Mountings**	Track
System power (W)	6	**Environment**	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20
UGRL	5
Efficiency (lm/W)	49.67



Luminous flux luminaire
298 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	2093	0.35
2	523	0.70
3	233	1.06
4	131	1.41
5	84	1.76

Electrical

Voltage (V)	24	**Emergency**	Without
Current (mA)	450	**Insulation class**	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		

Physical

Color	Chrome	**Spot diameter (mm)**	33
Orientation	Adjustable	**Length (mm)**	33
Weight (kg)	0.22	**Lifespan (L70 B10)**	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories included (honeycomb and screening crosspiece).