


Atom 120 Casambi integrated

New



09.3940.40 - White

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




Main specifications

Number of heads	1	Net lumen (lm)	440
Lamp category	LED	Mountings	Track
Power (W)	8W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle: 14°

h(m) E(lx) D(m)

1 5878 0.24

2 1469 0.49

3 653 0.73

4 367 0.97

5 235 1.21

Luminous flux luminaire
440 lm

Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	FLOS smart control, Electronic dimmable CASAMBI		
Emergency	Without		

Physical

Color	White	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	33
Weight (kg)	0.22		
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)