



New

### 09.3941.CZ - Bronze


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

#### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 433    |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 8W    | Environment    | Indoor |
| CCT (K)         | 2700K |                |        |
| CRI             | 90    |                |        |

#### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 13        |
| Beam angle C90-270 (°) | 13        |



Beam Angle: 14°

h(m) E(lx) D(m)

1 5843 0.24

2 1461 0.48

3 649 0.72

4 365 0.95

5 234 1.19

Luminous flux luminaire  
433 lm

#### Electrical

|             |                                                 |                  |     |
|-------------|-------------------------------------------------|------------------|-----|
| Voltage (V) | 24.00                                           | Insulation class | III |
| Dimmable    | Yes                                             |                  |     |
| Driver      | Remote                                          |                  |     |
| Driver type | FLOS smart control, Electronic dimmable CASAMBI |                  |     |
| Emergency   | Without                                         |                  |     |

#### Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | Bronze     | Spot diameter (mm) | 33 |
| Orientation  | Adjustable | Length (mm)        | 33 |
| Weight (kg)  | 0.22       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

#### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

