



Atom 120 Casambi integrated



09.3942.14 - Black

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.


Main specifications

Number of heads	1
amp category	LED
Power (W)	8W
CCT (K)	3000K
CRI	90

Net lumen (lm) 373 Mountings Track Environment Indoor

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20



Luminous flux luminaire 373 lm

Beam Angle:		20°
h(m)	E(lx)	D(m
1	2624	0.35
2	656	0.70
3	292	1.06
4	164	1.41
5	105	1.76

	81		
16		20	
122		1	138
	ø33		

(F)	IP	
	20	

F	lectrical
	-cuicai

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
Driver type	FLOS smart
	control,
	Electronic
	dimmable

CASAMBI

Emergency Without

Insulation class

Physical		
Color	Black	Spot diameter (mm) 33
Orientation	Adjustable	Length (mm) 33
Weight (kg)	0.22	
Tilt (°)	90	
Rotation (°)	360	

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)