



Atom 120 Casambi integrated



09.3943.14 - Black

 ${\sf LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.


Main specifications

Number of heads	1	Net lumen (lm)
Lamp category	LED	Mountings
Power (W)	8W	Environment
CCT (K)	2700K	
CRI	90	

Mountings Track Environment Indoor

Optical

Direct
Power LED
Symmetric
Medium
20
20



Ш

364

639 0.70 3 284 1.06 4 160 1.41 102 1.76

Beam Angle:

h(m)

 $E(I_X)$

2557

20°

D(m)

0.35

Luminous flux iun
364 lm

Electrical

Voltage (V)	24.00	Insulation class
Dimmable	Yes	
Driver	Remote	
Driver type	FLOS smart	
	control,	
	Electronic	
	dimmable	

CASAMBI

Without

Emergency Physical

Color	Black	Spot diameter (mm) 33
Orientation	Adjustable	Length (mm) 33
Weight (kg)	0.22	
Tilt (°)	90	
Rotation (°)	360	

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

