



## Atom 120 Casambi integrated

New

### 09.3943.14A - Black


Accent lighting LED module. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	364
Power (W)	8W	Mountings	Track
System power (W)	8	Environment	Indoor dry location
CCT (K)	2700K		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20
UGRL	5
Efficiency (lm/W)	45.5



Beam Angle: 20°

h(m) E(lx) D(m)

1 2557 0.35

2 639 0.70

3 284 1.06

4 160 1.41

5 102 1.76

Luminous flux luminaire  
364 lm

### Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	600	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded Dimmable Casambi		

### Physical

Color	Black	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	33
Weight (kg)	0.22	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

