

## Atom 200 Casambi integrated

■ 09.3950.06 - Chrome



LED general lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.

LED general lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	424
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	10.5W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	110
<b>Beam angle C90-270 (°)</b>	110



Beam Angle: 110°		
h(m)	E(lx)	D(m)
1	156	2.86
2	39	5.73
3	17	8.59
4	10	11.45
5	6	14.32

Luminous flux luminaire  
424 lm



### Electrical

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	FLOS smart control, Electronic dimmable CASAMBI		
<b>Emergency</b>	Without		

### Certification / Marking



### Physical

<b>Color</b>	Chrome	<b>Spot diameter (mm)</b>	192
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	192
<b>Weight (kg)</b>	0.47		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)