

Atom 200 Casambi integrated

09.3950.40 - White



LED general lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.

LED general lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.




Main specifications

Number of heads	1	Net lumen (lm)	424
Lamp category	LED	Mountings	Track
Power (W)	10.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		


Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Beam Angle:	110°		
	h(m)	E(lx)	D(m)
1	156	2.86	
2	39	5.73	
3	17	8.59	
4	10	11.45	
5	6	14.32	

Luminous flux luminaire
424 lm



Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	FLOS smart control, Electronic dimmable CASAMBI		
Emergency	Without		

Certification / Marking



Physical

Color	White	Spot diameter (mm)	192
Orientation	Adjustable	Length (mm)	192
Weight (kg)	0.47		
Tilt (°)	90		
Rotation (°)	360		

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)