

## Atom 200 Casambi integrated

■ 09.3950.CZ - Bronze



LED general lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.

LED general lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.




### Main specifications

Number of heads	1	Net lumen (lm)	424
Lamp category	LED	Mountings	Track
Power (W)	10.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		


### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Beam Angle:	110°		
	h(m)	E(lx)	D(m)
1	156	2.86	
2	39	5.73	
3	17	8.59	
4	10	11.45	
5	6	14.32	

Luminous flux luminaire  
424 lm



### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	FLOS smart control, Electronic dimmable CASAMBI		
Emergency	Without		

### Physical

Color	Bronze	Spot diameter (mm)	192
Orientation	Adjustable	Length (mm)	192
Weight (kg)	0.47		
Tilt (°)	90		
Rotation (°)	360		

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

### Certification / Marking

