



Atom 200 Casambi integrated



09.3951.18 - Deep Brown

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.


Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	395
Power (W)	10.5W	Mountings	Track
System power (W)	10.5	Environment	Indoor dry location

2700K

CCT (K) Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110
UGRL	23
Efficiency (lm/W)	37.62



1 145 2.86 36 5.73 3 16 8.59 4 9 11.45 6 14.32

h(m)

Beam Angle: 110° E(lx)

D(m)

Luminous flux lumi
395 lm


Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	420	Insulation class	III
Dimmable	Yes		
Driver	Remote		
	excluded		
Driver type	Dimmable		

Casambi

Physical

Color	Deep Brown	Spot diameter (mm)	192
Orientation	Adjustable	Length (mm)	192
Weight (kg)	0.47	Lifespan (L70 B10)	L80B50
Tilt (°) Rotation (°)	90 360	Ellespail (E70 B10)	L00D30















Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)