

## Atom 200 Casambi integrated

New

09.3951.40 - White

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.




### Main specifications

Number of heads	1	Net lumen (lm)	395
Lamp category	LED	Mountings	Track
Power (W)	10.5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Beam Angle: 110°

h(m)	E(lx)	D(m)
1	145	2.86
2	36	5.73
3	16	8.59
4	9	11.45
5	6	14.32

Luminous flux luminaire  
395 lm

### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

### Physical

Color	White	Spot diameter (mm)	192
Orientation	Adjustable	Length (mm)	192
Weight (kg)	0.47		
Tilt (°)	90		
Rotation (°)	360		

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

