Atom 200 Casambi integrated

New

09.3951.40 - White

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.

Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	395
Power (W)	10.5W	**Mountings**	Track
System power (W)	10.5	**Environment**	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110
UGRL	23
Efficiency (lm/W)	37.62



Luminous flux luminaire
395 lm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	145	2.86
2	36	5.73
3	16	8.59
4	9	11.45
5	6	14.32

Electrical

Voltage (V)	24	**Emergency**	Without
Current (mA)	420	**Insulation class**	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		



Physical

Color	White	**Spot diameter (mm)**	192
Orientation	Adjustable	**Length (mm)**	192
Weight (kg)	0.47	**Lifespan (L70 B10)**	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

IP 20