


Atom 200 Casambi integrated

New

09.3951.CZ - Bronze

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	395
Power (W)	10.5W	Mountings	Track
System power (W)	10.5	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110
UGRL	23
Efficiency (lm/W)	37.62



Beam Angle: 110°

h(m)	E(lx)	D(m)
1	145	2.86
2	36	5.73
3	16	8.59
4	9	11.45
5	6	14.32

Luminous flux luminaire
395 lm

Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	420	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
	Casambi		

Physical

Color	Bronze	Spot diameter (mm)	192
Orientation	Adjustable	Length (mm)	192
Weight (kg)	0.47	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

