



Atom 90

09.3831.1AA - Anodic Ice

LED accent lighting module to be installed in the Diversion system. Electronic DC/DC converter incorporated. System controlled by 1-10V, DALI or Casambi. Broadcast control system. Dimmer not included. To individually control the spots via Casambi, choose the Casambi version of spots. Accessories included (honeycomb and screening crosspiece).


Main specifications

Number of heads	1	Net lumen (lm)	224
Lamp category	LED	Mountings	Track
Power (W)	5.5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		




Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14



Beam Angle:	14°		
	h(m)	E(lx)	D(m)
	1	2558	0.25
	2	640	0.51
	3	284	0.76
	4	160	1.02
	5	102	1.27

Luminous flux luminaire
224 lm



Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Anodic Ice	Spot diameter (mm)	23
Orientation	Adjustable	Length (mm)	90
Weight (kg)	0.1		
Tilt (°)	90		
Rotation (°)	360		

