



Atom 90

■ 09.3832.14A - Black


Accent lighting LED module. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1-10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 289 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 5.5W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical


| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 25 |
| Beam angle C90-270 (°) | 25 |



Beam Angle: 25°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1500 | 0.45 |
| 2 | 375 | 0.89 |
| 3 | 167 | 1.34 |
| 4 | 94 | 1.79 |
| 5 | 60 | 2.23 |

Luminous flux luminaire
289 lm



Electrical

| | | | |
|--------------------|---|-------------------------|-----|
| Voltage (V) | 24 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1 | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|---------------------------|----|
| Color | Black | Spot diameter (mm) | 23 |
| Orientation | Adjustable | Length (mm) | 23 |
| Weight (kg) | 0.1 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Accessories included (honeycomb and screening crosspiece).

