



### Atom 90

#### 09.3832.1A - Anodic Ice


LED accent lighting module to be installed in the Diversion system. Electronic DC/DC converter incorporated. System controlled by 1-10V, DALI or Casambi. Broadcast control system. Dimmer not included. To individually control the spots via Casambi, choose the Casambi version of spots. Accessories included (honeycomb and screening crosspiece).

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 240    |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 5.5W  | Environment    | Indoor |
| CCT (K)         | 3000K |                |        |
| CRI             | 90    |                |        |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 26        |
| Beam angle C90-270 (°) | 26        |



Beam Angle: 25°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 1500 | 0.45  |      |
| 2 | 375  | 0.89  |      |
| 3 | 167  | 1.34  |      |
| 4 | 94   | 1.79  |      |
| 5 | 60   | 2.23  |      |

Luminous flux luminaire  
289 lm



### Electrical

|             |                                                                                                           |                  |     |
|-------------|-----------------------------------------------------------------------------------------------------------|------------------|-----|
| Voltage (V) | 24.00                                                                                                     | Insulation class | III |
| Dimmable    | Yes                                                                                                       |                  |     |
| Driver      | Remote                                                                                                    |                  |     |
| Driver type | Electronic,<br>Electronic dimmable<br>CASAMBI,<br>Electronic dimmable 1-<br>10V, Electronic dimmable DALI |                  |     |
| Emergency   | Without                                                                                                   |                  |     |

### Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | Anodic Ice | Spot diameter (mm) | 23 |
| Orientation  | Adjustable | Length (mm)        | 90 |
| Weight (kg)  | 0.10       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

