21°

D(m) 0.37

0.73

1.10

1.47

1.84

Beam Angle:

h(m) E(lx)

2

3

1508

377

168







### 09.3832.40 - White


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

### Main specifications

Number of heads	1	Net lumen (lm)	240
Lamp category	LED	Mountings	Track
Power (W)	5.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

## Optical

Direct
Power LED
Symmetric
Medium
26
26



30° 1508 cd 30° 5 60 Luminous flux luminaire 240 lm

	81		
90,5 26,5		20	117
	ø24		



	lectrical
-	I ACT PICA
_	i <del>c</del> cii icai

Voltage (V)	24.00	Insulation class
Dimmable	Yes	
Driver	Remote	
Driver type	Electronic,	
	Electronic	
	dimmable	
	CASAMBI,	
	Electronic	
	dimmable 1-	
	10V, Electronic	
	dimmable DALI	

Emergency

# Physical

Color	White	Spot diameter (mm)	23
Orientation	Adjustable	Length (mm)	23
Weight (kg)	0.10	_	
Tilt (°)	90		
Rotation (°)	360		

Without

### Note

Accessories included (honeycomb and screening crosspiece).