



Atom 90

09.3833.1AA - Anodic Ice

LED accent lighting module to be installed in the Diversion system. Electronic DC/DC converter incorporated. System controlled by 1-10V, DALI or Casambi. Broadcast control system. Dimmer not included. To individually control the spots via Casambi, choose the Casambi version of spots. Accessories included (honeycomb and screening crosspiece).


Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 261 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 5.5W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |




Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 25 |
| Beam angle C90-270 (°) | 25 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 25° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 1355 | 0.45 | |
| 2 | 339 | 0.89 | |
| 3 | 151 | 1.34 | |
| 4 | 85 | 1.79 | |
| 5 | 54 | 2.23 | |

Luminous flux luminaire
261 lm



Electrical

| | | | |
|--------------------|---|-------------------------|-----|
| Voltage (V) | 24 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable, Dimmable 1-10V, Dimmable DALI 1 | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|---------------------------|----|
| Color | Anodic Ice | Spot diameter (mm) | 23 |
| Orientation | Adjustable | Length (mm) | 90 |
| Weight (kg) | 0.1 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

