



## Atom 90

09.3833.40 - White

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. To individually control the lights, select integrated Casambi versions.


### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	217
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power</b>	5.5W	<b>Environment</b>	Indoor
<b>CCT</b>	2700K		
<b>CRI</b>	90		



### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	26
<b>Beam angle C90-270 (°)</b>	26



Beam Angle: 25°		
h(m)	E(lx)	D(m)
1	1355	0.45
2	339	0.89
3	151	1.34
4	85	1.79
5	54	2.23




Luminous flux luminaire  
261 lm



### Electrical

<b>Voltage (V)</b>	24.00	<b>Emergency</b>	Without
<b>Lamp holder</b>	LED	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable CASAMBI, Electronic dimmable push, Electronic dimmable 1- 10V, Electronic dimmable DALI		

### Certification / Marking



### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	23
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	23
<b>Weight (kg)</b>	0.10		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Accessories included (honeycomb and screening crosspiece).