



Atom 90 Casambi integrated



9.3930.14A - Black

Accent lighting LED module. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	5.5W
System power (W)	5.5
CCT (K)	3000K

CRI 90 Net lumen (lm) 247 Mountings Track

Environment Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14
UGRL	2
Efficiency (lm/W)	44.91



Without

Emergency

Insulation class

2832 0.25 708 0.51 3 315 0.76 4 177 1.02 113 1.27

E(lx)

Beam Angle:

h(m)

14°

D(m)


247 lm

Electrical

Voltage (V)	24
Current (mA)	400
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmable
	Casambi

Physical

Color	Black	Spot diameter (mm) 23
Orientation	Adjustable	Length (mm) 23
Weight (kg)	0.1	Lifespan (L70 B10) L80B50
Tilt (°)	90	
Rotation (°)	360	













Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)