



Atom 90 Casambi integrated



■ 09.3930.CZA - Bronze

Accent lighting LED module. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

Main specifications


Number of heads	1	C
Lamp category	LED	N
Power (W)	5.5W	N
System power (W)	5.5	Е
CCT (K)	3000K	

CRI 90 247 Net lumen (lm) Mountings Track

Environment Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14
UGRL	2
Efficiency (lm/W)	44.91



Without

 $E(I_X)$ D(m) h(m) 2832 0.25 708 0.51 3 315 0.76 4 177 1.02 113 1.27

Beam Angle:

14°

Luminous flux luminaire 247 lm

Emergency

Insulation class


-	lectrica

voitage (v)	24
Current (mA)	400
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmable

Physical

Color	Bronze	Spot diameter (mm)	23
Orientation	Adjustable	Length (mm)	23
Weight (kg)	0.1	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Casambi















Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)