

Atom 90 Casambi integrated

New

09.3931.06A - Chrome

Accent lighting LED module. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	214
Power (W)	4.7W	Mountings	Track
System power (W)	4.7	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14
UGRL	2
Efficiency (lm/W)	45.53



Beam Angle:	14°		
	h(m)	E(lx)	D(m)
1	2448	0.25	
2	612	0.51	
3	272	0.76	
4	153	1.02	
5	98	1.27	

Luminous flux luminaire
214 lm

Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	330	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

Physical

Color	Chrome	Spot diameter (mm)	23
Orientation	Adjustable	Length (mm)	23
Weight (kg)	0.1	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

