


## Atom 90 Casambi integrated

■ 09.3931.14 - Black



LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included.

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	224
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	5.5W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	15
<b>Beam angle C90-270 (°)</b>	15



<b>Beam Angle:</b>	14°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	2558	0.25	
2	640	0.51	
3	284	0.76	
4	160	1.02	
5	102	1.27	

Luminous flux luminaire  
224 lm

### Electrical

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	FLOS smart control, Electronic dimmable CASAMBI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black	<b>Spot diameter (mm)</b>	23
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	23
<b>Weight (kg)</b>	0.10		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time).

### Certification / Marking

