



## Atom 90 Casambi integrated

New

09.3932.06A - Chrome


Accent lighting LED module. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	261
<b>Power (W)</b>	4.7W	<b>Mountings</b>	Track
<b>System power (W)</b>	4.7	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	25
<b>Beam angle C90-270 (°)</b>	25
<b>UGRL</b>	3
<b>Efficiency (lm/W)</b>	55.53



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1352	0.45
2	338	0.89
3	150	1.34
4	85	1.79
5	54	2.23

Luminous flux luminaire  
261 lm



### Electrical

<b>Voltage (V)</b>	24	<b>Emergency</b>	Without
<b>Current (mA)</b>	330	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable Casambi		

### Physical

<b>Color</b>	Chrome	<b>Spot diameter (mm)</b>	23
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	23
<b>Weight (kg)</b>	0.1	<b>Lifespan (L70 B10)</b>	L80B50
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

