



New

**09.3933.06 - Chrome**


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

**Main specifications**

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 250    |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 4.7W  | Environment    | Indoor |
| CCT (K)         | 2700K |                |        |
| CRI             | 90    |                |        |

**Optical**

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 26        |
| Beam angle C90-270 (°) | 26        |



Beam Angle: 25°

h(m) E(lx) D(m)

1 1355 0.45

2 339 0.89

3 151 1.34

4 85 1.79

5 54 2.23

Luminous flux luminaire  
261 lm

**Electrical**

|             |                                                 |                  |     |
|-------------|-------------------------------------------------|------------------|-----|
| Voltage (V) | 24.00                                           | Insulation class | III |
| Dimmable    | Yes                                             |                  |     |
| Driver      | Remote                                          |                  |     |
| Driver type | FLOS smart control, Electronic dimmable CASAMBI |                  |     |
| Emergency   | Without                                         |                  |     |

**Physical**

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | Chrome     | Spot diameter (mm) | 23 |
| Orientation  | Adjustable | Length (mm)        | 23 |
| Weight (kg)  | 0.10       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

**Note**

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

