



09.3933.40A - White

Accent lighting LED module. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

Main specifications


Number of heads	1	CRI
Lamp category	LED	Net lum
Power (W)	5.5W	Mountin
System power (W)	5.5	Environ
CCT (K)	2700K	

90 men (lm) 261 ings Track

nment Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	25
Beam angle C90-270 (°)	25
UGRL	3
Efficiency (lm/W)	47.45



Luminous flux luminaire 261 lm

Without

Beam Angle:		25°
<u>h(m)</u>	E(l x)	D(m)
1	1355	0.45
2	339	0.89
3	151	1.34
4	85	1.79
5	54	2.23

Electrical

Voltage (V)	24	Emergency
Current (mA)	400	Insulation c
Dimmable	Yes	
Driver	Remote	
	excluded	
Driver type	Dimmable	

Casambi

Physical

Color	White	Spot diameter (mm) 2	23
Orientation	Adjustable	Length (mm)	23
Weight (kg)	0.1	Lifespan (L70 B10)	L80B50
Tilt (°)	90	•	
Rotation (°)	360		



26,5









Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)