


Battery No Trim Small 2L

■ 04.6475.14BNT - Black

Recessed luminaire with LED light source. Power supply not included. Requires one power supply for each optic body.




**Inaccessible ceiling
* Accessible ceiling: modular/open

Main specifications

Lamp category	LED	Mountings	Ceiling recessed
Power (W)	2 x 16.5W	Environment	Indoor
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	1768		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Flood



Beam Angle: 29°

h(m)	E(lx)	D(m)
1	5391	0.52
2	1348	1.04
3	599	1.56
4	337	2.08
5	216	2.59

Luminous flux luminaire
1768 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		
Emergency	Without		


Physical

Color	Black
Orientation	Adjustable
Recessed depth (mm)	146
Weight (kg)	1.89
Rotation (°)	40

Note

Pre-installation frame must be ordered separately

Certification / Marking



Battery No Trim Small 2L



Honeycomb
08.8495.14



BLUE FILTER
08.8503.64.OD



SKY BLUE FILTER
08.8503.65.OD



AMBER FILTER
08.8503.66.OD



RED FILTER
08.8503.67.OD



HOT LIGHT
08.8503.69



COLD LIGHT
08.8503.CL



DAYLIGHT
08.8503.DL



NEODIMIUM
08.8503.ND



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200mA – 8,5W / 250mA – 11W / 300mA – 13W / 350mA – 15W / 400mA – 17,5W / 450mA 19,5W / 500mA – 22W.
60.9160



Continuous current power supply of 13-20W, 110*/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.
60.9188



Constant Current Power Supply for LED. Dimmable DALI. 10-20W
60.8847



Continuous current power supply of 12-20W, 110*/240V – 50/60Hz with power current selected through adjustable. Regulable DALI 1 y DALI 2
60.9222



Continuous current power supply, Mains dimming 220/240V – 50/60Hz, 12-20W
60.9467



Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 35W – 650mA / 36W – 700 mA.
60.9207



Pre-installation frame

