


Battery No Trim Small 4L Square


■ 04.6485.14BNT - Black

Recessed luminaire with LED light source. Power supply not included. Requires one power supply for each optic body.



**Inaccessible ceiling

* Accessible ceiling: modular/open




Main specifications

Number of heads	4	Net lumen (lm)	1768
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	16.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	29
Beam angle C90-270 (°)	29



Beam Angle: 29°

h(m) E(lx) D(m)

1 5391 0.52

2 1348 1.04

3 599 1.56

4 337 2.08

5 216 2.59

Luminous flux luminaire
1768 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI 2, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming		
Emergency	Without		

Physical

Color	Black
Orientation	Adjustable
Recessed depth (mm)	146
Weight (kg)	2.92
Rotation (°)	40

Note

Pre-installation frame must be ordered separately

Battery No Trim Small 4L Square



Continuous current power supply,
Mains dimming, leading & trailing edge
220/240V – 50/60Hz, 300mA-14W /
350mA-17W / 400mA-19W /
450/500/600/650/700/750/800/900mA –
20W
60.9467

Non dimmable continuous current
power supply of 220/240V – 50/60Hz
with power current selected through
adjustable with switch 200 mA – 8,5W /
300 mA – 13W / 350 mA – 15W / 400 mA
– 17,5W / 450 mA – 19,5W / 500 mA –
22W
60.9160

Pre-installation frame
08.8526.00



SKY BLUE FILTER
08.8503.65.OD

DAYLIGHT
08.8503.DL

Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/1000/1050mA – 38W
60.9207



HOT LIGHT
08.8503.69



RED FILTER
08.8503.67.OD



AMBER FILTER
08.8503.66.OD



Continuous current power supply of
13-20W, 110/240V – 50/60Hz with power
current selected through adjustable
300 mA – 15W / 350 mA – 18W /
400/450/500/550/600/
650/700/750/800/850/900 mA – 15W.
switch. 0/1-10V or push dimming
60.9188



Honeycomb
08.8495.14



Continuous current power supply of
12-20W, 110/240V – 50/60Hz with power
current selected through adjustable
350mA – 17W / 400mA – 19W / 450 / 550
/ 600 / 700mA – 20W regulable Dali 1 y
Dali 2
60.9222



COLD LIGHT
08.8503.CL



Continuous current power supply of
10-20W, 110/240V – 50/60Hz with power
current selected through adjustable
250 mA – 10W / 350 mA – 15W / 400 mA
450 / 500 / 550 / 600 / 650 / 700 mA – 20W regulable Dali 1 y
Dali 2



NEODIMIUM
08.8503.ND

60.8847



BLUE FILTER
08.8503.64.OD