



Battery Trim Small 3L

■ 04.6480.14B - Matt Black

Recessed luminaire with LED light source. Power supply not included. Requires one power supply for each optic body.




Main specifications

Number of heads	3	Net lumen (lm)	1768
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	16.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	29
Beam angle C90-270 (°)	29



Beam Angle: 29°

h(m)	E(lx)	D(m)
1	5391	0.52
2	1348	1.04
3	599	1.56
4	337	2.08
5	216	2.59

Luminous flux luminaire
1768 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI 2, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming		
Emergency	Without		

Physical

Color	Matt Black
Orientation	Adjustable
Recessed depth (mm)	149
Weight (kg)	1.61
Rotation (°)	40

Battery Trim Small 3L



Honeycomb
08.8495.14



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188



Continuous current power supply, Mains dimming, leading & trailing edge 220/240V – 50/60Hz, 300mA-14W / 350mA-17W / 400mA-19W / 450/500/600/650/700/750/800/900mA – 20W
60.9467



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W
60.9160



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.
60.8847



BLUE FILTER
08.8503.64.OD



SKY BLUE FILTER
08.8503.65.OD



AMBER FILTER
08.8503.66.OD



NEODIMIUM
08.8503.ND



HOT LIGHT
08.8503.69



COLD LIGHT
08.8503.CL



Continuous current power supply of
12-20W, 110/240V – 50/60Hz with power
current selected through adjustable
350mA – 17W / 400mA – 19W / 450 / 550
/ 600 / 700mA – 20W regulable Dali 1 y
Dali 2
60.9222



DAYLIGHT
08.8503.DL



RED FILTER
08.8503.67.OD



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
750mA-39W / 800mA-40W / 850mA-42W / 900mA-44W / 950mA-46W / 1000mA-48W
