

Belt L 3000 mm Dimmable 1-10V

New

■ 03.8501.GN.1V - Green Leather

Electromechanical profile for interior use with integrated linear lighting for suspended installation available with 2 or 3 m lengths. Installation via suspension straps on the ceiling and remote power kit, to be ordered separately. Up&Down system controlled via DALI or CASAMBI individually and via 1-10V all together (Broadcast).


Electromechanical profile for interior use with integrated linear lighting for suspended installation available with 2 or 3 m lengths. Installation via suspension straps on the ceiling and remote power kit, to be ordered separately. Up&Down system controlled via DALI or CASAMBI individually and via 1-10V all together (Broadcast).

Main specifications

Number of heads	1	Net lumen (lm)	2542
Lamp category	LED	Mountings	Suspension
Power (W)	83W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	95		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	60
Beam angle C90-270 (°)	100
Beam angle ind (°)	70
Beam angle ind C90-270 (°)	90



Beam Angle: 60°

h(m)	E(lx)	D(m)
1	776	1.16
2	194	2.31
3	86	3.47
4	48	4.63
5	31	5.79

Luminous flux luminaire
2542 lm

Electrical


Driver	Remote excluded
Driver type	Dimmable 1-10V
Emergency	Without
Insulation class	III

Physical

Color	Green Leather
Orientation	Fixed
Weight (kg)	3.3
Length (mm)	3000

Note

Power kit and suspension straps sold separately. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.



Belt L 3000 mm Dimmable 1-10V




Wall Mounted Feed Box
08.0182.00



Double Surface Feed Box
08.0195.00



Suspension strap L 2000 mm
03.8511.GN



Double Ceiling Feed Box
08.0181.00



Suspension strap L 2500 mm
03.8514.GN



Individual Ceiling Feed Box
08.0180.00



48-V Power Loop L 2500 mm
03.8521.GN



Surface Driver Box 96W – 48V, 110-240V.
06.0173.14



Individual Surface Feed Box
08.0194.00



48-V Power Loop L 1500 mm
03.8520.GN



Suspension strap L 3000 mm
03.8512.GN



48-V Power Loop L 3500 mm
03.8522.GN



LED power supply source for remote
installation, 48V/120W. 220/240 Vac
60.9170



LED Power Supply Source for remote
installation. 48V. 100Vac (150W)-240Vac
(200W)
60.9607



Suspension strap L 1000 mm
03.8510.GN



Suspension strap L 1500 mm
03.8513.GN